



## FEATURES



### OHV

Over Head Valve easy to maintenance



### OIL LEVEL ALARM

When the oil level is low that the engine will not start.



### AVR

AVR is a device often solid state, for controlling the output voltage of a generator.



### CIRCUIT PROTECTOR

Circuit Protector is a device capable of carrying and interrupting both load and fault current upto a certain rating.



### CHOKE SYSTEM

When the cold weather, choke system aid to operate the engine

## GENERAL SPECIFICATIONS

Mono-Phase, 50 Hz, PF 1

AC Rated Power (kW)	0,85
Maximum Power (kW)	0,95
AC Rated Current	3,9
DC Rated Current	6
Voltage (V)	230
Frequency (Hz)	50
Phase N.	1
Power Factor	0,8
Fuel Consumption (L/h.)	0,5
Run Time (Hour)	5
Noise Level (dB(A))	64





## ENGINE SPECIFICATIONS

Speed (rpm)	3000
Cylinder N.	1
Cylinder Bulk	55
Fuel Type	Gasoline
Oil Capacity (L.)	0,4
Fuel Tank Capacity (L.)	2,1
Start Type	Rope

## DIMENSIONS AND WEIGHT

Width (mm.)	460
Lenght (mm.)	250
Height (mm.)	400
Dry Weight (kg.)	15