



FEATURES



OHV

Over Head Valve easy to maintenance



OIL LEVEL ALARM

When the oil level is low that the engine will not start. voltage of a generator.



AVR

AVR is a device often solid state, for controlling the output



CIRCUIT PROTECTOR

Circuit Protector is a device capable of carrying and interrupting both load and fault current upto a certain rating.



VOLTMETER

It is a gauge for out put voltage of generator set.



CHOKE SYSTEM

engine.

GENERAL SPECIFICATIONS

Mono-Phase, 50 Hz, PF 1

AC Rated Power (kW)	1,7
Maximum Power (kW)	1,9
AC Rated Current	7,7
DC Rated Current (A)	6
Voltage (V)	230
Frequency (Hz)	50
Phase N.	1
Power Factor	0,80
Fuel Consumption (L/h.)	1,3
Run Time (Hour)	5
Noise Level (dB(A))	64



ENGINE SPECIFICATIONS

Speed (Rpm)	3000
Cylinder N.	1
Oil Capacity (L.)	0,4
Fuel Type	Gasoline
Fuel Tank Capacity (L.)	3,2
Start Type	Rope

DIMENSIONS AND WEIGHT

Width (mm.)	550
Lenght (mm.)	305
Height (mm.)	460
Dry Weight (kg.)	24,3